

# 

# **EXPERIENCE PROVEN** PERFORMANCE.

The Hauler 800, now available with an ELiTE® lithium drivetrain powered by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gas engine, gives you the power to accomplish any task on your course. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.



8.4 CU FT

CARGO BED

900 LB

TOWING CAPACITY

800 LB

VEHICLE LOAD CAPACITY

2 PASSENGER

SEATING

**ZERO MAINTENANCE** 

ELITE LITHIUM BATTERY





# **ELITE LITHIUM POWERTRAIN**

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

## **OPTIONS & ACCESSORIES**

- IntelliGauge™ (ELiTE Only)
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge

# CUSHMAN.COM

# HAULER 800

#### **BODY & CHASSIS**

| L | FRAME          | Welded Steel with E-Coat & DuraShield™ Powder Coat |  |
|---|----------------|--|--|
|   | BODY & FINISH  | Injection Molded TPO                               |  |
| [ | STANDARD COLOR | Forest Green                                       |  |

HAULER 800 ELITE

HAULER 800 GAS

# **DIMENSIONS**

| OVERALL LENGTH       | 110 in (279.4 cm)   |  |
|----------------------|---|--|
| OVERALL WIDTH        | 49 in (125 cm)  |  |
| OVERALL HEIGHT       | 47 in (119.4 cm) (No Canopy)<br>69.5 in (176.5 cm) (w/ Struts & Roof) |  |
| WHEEL BASE           | 65.5 in (166.4 cm)  |  |
| WHEEL TRACK          | 37 in (94 cm) Front / 38 in (96.5 cm) Rear                            |  |
| GROUND CLEARANCE     | 4.3 in (10.9 cm)  |  |
| CARGO BOX CAPACITY   | 8.4 cu ft (0.24 cu m)   |  |
| CARGO BOX DIMENSIONS | 28.5 in (L) x 44.5 in (W) x 12 in (D)<br>(72.4 cm x 113 cm x 30.5 cm) |  |
| CARGO BOX MATERIAL   | Roto-Molded Polyethylene  |  |

## **POWER**

| POWER TRAIN        | 56.7V Li-Ion Battery                                | 4-Cycle, 24.5 cu in (401cc)                   |
|--------------------|---|---|
| VALVE TRAIN        | N/A   | Single Cylinder OHV                           |
| HORSEPOWER (KW)    | 11.7 hp (8.7 kW) Peak                               | 13.5 hp (10.1 kW)                             |
| ELECTRICAL SYSTEM  | 48V Primary, 12V Auxiliary                          | Starter/Generator.<br>Solid State Reg.        |
| BATTERY (QTY/TYPE) | 2.2 Elite - Single Pack                             | One, 12V Maintenance Free                     |
| KEY OR PEDAL START | Pedal   |   |
| AIR CLEANER        | N/A   | Replaceable Industrial<br>Rated Dry Cartridge |
| LUBRICATION        | N/A   | Pressurized Oil System                        |
| OIL FILTER         | N/A   | Spin-On                                       |
| COOLING SYSTEM     | N/A   | Air Cooled                                    |
| FUEL CAPACITY      | N/A   | 5.96 Gallon (22.6 L) tank                     |
| DRIVE TRAIN        | Motor Shaft Direct Drive                            | Continuously Variable<br>Transmission         |
| TRANSAXLE          | Differential w/ Helical Gears                       |   |
| GEAR SELECTION     | Dash Mount Forward-Neutral-<br>Reverse / Key Switch | Forward - Reverse                             |
| REAR AXLE RATIO    | 16.99:1   | 11.47: 1 (Forward)<br>14.35:1 (Reverse)       |

# PERFORMANCE

| SEATING CAPACITY         | 2-Person (Bench)                           |  |
|--------------------------|--|--|
| WEIGHT W/O BATTERIES     | 753 lb (342 kg)                            | 761 lb ( 345.2 kg)                         |
| CURB WEIGHT              | 800 lb (363 kg)                            | 791 lb (359 kg)                            |
| VEHICLE LOAD CAPACITY    | 800 lb (362.9 kg)                          |  |
| BED LOAD CAPACITY        | 400 lb (181.4 kg)                          |  |
| TOWING CAPACITY          | 900 lb (408.2 kg)                          |  |
| OUTSIDE CLEARANCE CIRCLE | 18.9 ft (5.8 m)                            |  |
| SPEED                    | 16.5 mph ± 0.5 mph<br>(26.5 kph ± 0.8 kph) | 14.5 mph ± 0.5 mph<br>(23.3 kph ± 0.8 kph) |

## STEERING & SUSPENSION

| STEERING      | Self-Compensating Rack and Pinion         |   |  |
|---------------|---|---|--|
| SUSPENSION    | Leaf Springs w/ Hydraulic Shock Absorbers |   |  |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum |   |  |
| PARKING BRAKE | Automatic Electro-Magnetic                | Self-Compensating,<br>Single-Point Engagement |  |
|               |   |   |  |

TIRES (FRONT & REAR) 18 x 8.5 -8 (6 Ply Tires)

