

ELITE® SERIES

UNLOCK THE FULL POTENTIAL OF THE WORKDAY.

The Hauler PRO Series has raised the bar for utility vehicles on the course with its reduced weight, remarkable range, and higher ground clearance on the Hauler PRO-X. The ELITE lithium drivetrain powered by Samsung SDI battery technology provides unmatched efficiency, zero emissions and reduced turf compaction, creating a vehicle that works just as hard as you do.



ZERO Maintenance

ELITE LITHIUM BATTERY

1500 LB / 1200 LB TOWING CAPACITY

1200 LB / 900 LB LOAD CAPACITY

12 CU FT CARGO BED







HAULER PRO

HAULER PRO-X

ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Automatic Park Brake
- Multifunction SOC/Speedometer Gauge
- Limited Slip Differential

OPTIONS & ACCESSORIES

- IntelliGauge
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Flat DOT Windshield
- Fold Down Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Aluminum Flat Bed
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Ladder/Hoop Rack for Aluminum Bed
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger
- Drop-In Refresher for Plastic Bed Only
- Differential Scuff Guard

HAULER® PRO / ELITE SERIES

HAULER PRO

HAULER PRO-X

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat		
BODY & FINISH	Injection Molded TPO		
STANDARD COLOR	Forest Green		

DIMENSIONS

OVERALL LENGTH	119 in (302 cm)		
OVERALL WIDTH	49 in (125 cm)		
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)	77 in (196 cm)	
WHEEL BASE	76.8 in (195 cm)	77.5 in (196.9 cm)	
FRONT WHEEL TRACK	35 in (88.9 cm)	38.0 in (96.56 cm)	
REAR WHEEL TRACK	38.5 in (97.8 cm)		
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	
CARGO BOX CAPACITY	12 cu ft (0.34 cu m)		
CARGO BOX DIMENSIONS	39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)		
CARGO BOX MATERIAL	Roto-Molded Polyethylene		

POWER

POWER SOURCE	56.7V Li-Ion Battery	
MOTOR TYPE	AC Induction	
HORSEPOWER (KW)	14.9 hp (11.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	
BATTERY (QTY/TYPE)	4.2 ELiTE - Twin Pack	
BATTERY CHARGER	811 Watt World Charger	
KEY OR PEDAL START	Pedal	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Limited-Slip Differential with Helical Gears	
SPEED CONTROLLER	350 Amp AC Controller	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse / Key Switch	
REAR AXLE RATIO	16.99:1	

PERFORMANCE

SEATING CAPACITY	2-Person	
CURB WEIGHT	926 lb (420 kg)	971 lb (440 kg)
BED LOAD CAPACITY	800 lb (363 kg)	500 lb (227 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	900 lb (408 kg)
SPEED	16.5 mph ± .05 mph (26.5 kph ± 0.8 kph)	
TOWING CAPACITY	1500 lb (680 kg) max	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)	

STEERING & SUSPENSION

Self-Compensating Rack & Pinion	
Leaf Springs w/ Hydraulic Shock Absorbers	
Dual Rear Wheel Mechanical, Self-Adjusting Drum	
Automatic Electro-Magnetic	
18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)
	Leaf Springs w/ Hydra Dual Rear Wheel Mechan Automatic Elei

